


## SECONDARY BATTERY CHARGED STATE MONITORING SYSTEM IN ELECTRONIC APPARATUS

**Patent number:** JP6163083  
**Publication date:** 1994-06-10  
**Inventor:** UENO HIROYASU  
**Applicant:** SHARP CORP  
**Classification:**  
 - international: H01M10/48  
 - european:  
**Application number:** JP19920306887 19921117  
**Priority number(s):**

### Abstract of JP6163083

**PURPOSE:** To precisely grasp the charged state of a secondary battery by software even in the state where a power source is cut.  
**CONSTITUTION:** A charging connection detecting circuit 21 is provided between a charging device 2 and a secondary battery 4, and a charging state monitoring arithmetic circuit 22 for receiving power supply from the secondary battery 4 is provided. The charging state monitoring arithmetic circuit 22 counts the clock from the real time clock 9 of a microcomputer part 5 when the charging connection detecting circuit 21 is laid in the detecting state, and stores the charging time  $t_c$  in a timer counter TCc in the RAM 8 of the microcomputer part 5. At power source input, the present charge residual capacity  $Q_0$  is calculated from the charge residual quantity  $Q_0$  at power source cut, the charge time  $t_c$  and the charged current value  $I_c$  by use of an application program 13, and displayed on a display device 11.



Data supplied from the esp@cenet database - Worldwide